


RIO-SUCTION STRAINERS

Technical Details

- Reusable Type
- Material - SS304
- 149 micron filtration
- Crimped all steel construction
- Max. Temp. - 240 F
- Firm Construction
- Sizes available from 1/2"-3"



Installation

Install the strainer in a horizontal position.
Tighten only with the hexagonal nut and not by any other means.

DIMENSIONS: inch (mm) FILTRATION: 100 mesh

MODEL NBR.	FLOW GPM (LPM)	THREAD NPT A	NUT SIZE B	OVERALL LENGTH C	DIA. D	WEIGHT lbs (kg)
RIO-005	5 (19)	1/2	1.1 (29)	3.9 (99)	2.5 (64)	.26 (.12)
RIO-007	8 (30)	3/4	1.3 (34)	5.2 (133)	2.5 (64)	.31 (.14)
RIO-013	10 (38)	1	1.7 (42)	6.2 (158)	2.5 (64)	.39 (.18)
RIO-016	20 (75)	1 1/4	1.9 (50)	7.0 (178)	2.5 (64)	.42 (.19)
RIO-053	30 (114)	1 1/2	2.6 (65)	7.6 (194)	3.3 (83)	.70 (.32)
RIO-055	50 (189)	2	3.0 (75)	8.3 (210)	4.0 (102)	.93 (.42)
RIO-092	75(284)	2 1/2	3.8 (97)	10.8 (274)	6.2 (158)	2.6 (1.2)
RIO-105	100(379)	3	4.3 (110)	10.8 (274)	6.2 (158)	2.6 (1.2)

